



CLEON[®]
Power Your World



INDUSTRIAL BATTERY



APPLICATION

- ▶ POWER & INFRA. PROJECTS
- ▶ TRACTION & MOTIVE POWER
- ▶ TELECOMMUNICATIONS
- ▶ RAILWAYS
- ▶ MINER'S CAP LAMS
- ▶ INSTITUTIONAL BATTERIES



**Superior
Capacity**



**Extended
Cycle Life**



**Reduced
Downtime**



**Fast &
Efficient Charging**



**Maximum
Energy**



**Climate
Resistance**



**Low
maintenance**



**Extended
life**

PRODUCT FEATURES:

1. PPCP CONTAINER.
2. PRESSURE DIE CASTED POSITIVE SPINES.
3. PASTED NEGATIVE PLATES.
4. HIGH POROSITY ENVELOPE SEPARATORS.
5. ELECTROLYTE LEVEL INDICATOR.
6. MICRO POROUS CERAMIC VENT PLUG.
7. SUPERIOR HIGH DISCHARGE PERFORMANCE CONFORMING TO IS: 1651.
8. HIGH AMPERE HOUR AND WATT HOUR EFFICIENCY.



TECHNICAL DATA

CONTAINER TYPE	CAPACITY @ C20	CONTAINER DIMENSION	GROSS BATTERY WEIGHT +/- 3%	NOMINAL VOLTAGE
	AH	L/W/H IN MM		
CS2V120	120AH	177 X 143 X 316	13	2 VOLT
CS2V200	200AH	219 X 176 X 335	17	2 VOLT
CS2V300	300AH	280 X 180 X 354	22	2 VOLT
CS2V400	400AH	267 X 174.5 X 447	28	2 VOLT
CS2V500	500AH	283 X 180 X 455	30	2 VOLT

Plot No 11 A, Sector - III, Vaishali, Ghaziabad, U.P - 201010, (INDIA)

Office No 27, 31st Floor, API World Tower, Sheikh Zayed Road
Dubai (UAE), Near Conrad Hotel

Email: export@cleonpowertech.in, cleonpowertech@gmail.com

Website: www.cleonglobal.com

Customer Care No: +91- 8287141365, +971- 509141365