



INVA SERIES



APPLICATION

- ▶ HOME APPLIANCES
- ▶ POWER BACK-UP
- ▶ OFFICE EQUIPMENT
- ▶ SECURITY INSTRUMENTS
- ▶ EMERGENCY LIGHTING
- ▶ SOLAR



MEETS IEC61427-1 SPEC




Low Maintenance



Superior Voltage



No Internal Packing



Faster Recharge



Increased Back-Up




Longer Life



Partial State of Charge Condition



Patented Container



**RANGE AVAILABLE
100 AH 260 AH**



PRODUCT FEATURES:

1. LONG SHELF LIFE- HEAVE DUTY TUBULAR PLATES TO PROVIDE EXCELLENT CYCLIC LIFE WITH DEEP CYCLE CAPABILITIES.
2. EXCELLENT PERFORMANCE UNDER EXTREME TEMPERATURE CONDITIONS.
3. THICK SPINES FOR EXCELLENT DISCHARGE PERFORMANCE ON HEAVY LOADS.
4. SPECIALLY DESIGNED VENT PLUGS FOR MINIMUM ACID FUMES MOST COMPACT TALL TUBULAR DESIGN WITH GLOBAL ACCEPTABILITY.
5. LEAK PROOF HEAT SEALED TALL PP CONTAINER.
6. SPECIAL ALLOYS FOR LOW MAINTENANCE OF BATTERIES.
7. DARAMIC PE SEPARATOR WITH HIGH POROSITY,. LOW ELECTRICAL RESISTANCE AND EXCELLENT OXIDATION RESISTANT.
8. EXTRA THICK SPINES CAST AT HIGH PRESSURE TO ENSURE MINIMUM CORROSION FOR RELIABILITY, EXTRA-LONG LIFE AND STRENGTH.
9. CERAMIC FIAME ARREST OR PREVENTS ELECTRICAL SPARK TO GO IN AND THEREFORE ENSURES HIGHEST DEGREE OF SAFETY FOR ALL DOMESTIC.
10. PATENTED DESIGN.



TECHNICAL DATA

CONTAINER TYPE	CAPACITY @ C20 AT 27°C	CONTAINER DIMENSION	LIFE CYCLE @ 80% DOD	GROSS BATTERY WEIGHT +/- 3%	BACKUP
	AH	L/W/H IN MM			
IT 500	12V 100 AH	510X190X440	1200+	50 KG	2HR:00 MIN @ 400 WATT
IT 500	12V 120 AH	510X190X440	1200+	53 KG	2HR:40 MIN @ 400 WATT
IT 500	12V 150 AH	510X190X440	1200+	57 KG	3HR:10 MIN @ 400 WATT
IT 500	12V 180 AH	510X190X440	1200+	60 KG	3HR:45 MIN @ 400 WATT
IT 500	12V 200 AH	510X190X440	1200+	63 KG	4HR:10 MIN @ 400 WATT
IT 500	12V 220 AH	510X190X440	1200+	65 KG	5HR:10 MIN @ 400 WATT
IT 500	12V 240 AH	510X190X440	1200+	69 KG	6HR:00 MIN @ 400 WATT
IT 500	12V 260 AH	510X190X440	1200+	72 KG	6HR:30 MIN @ 400 WATT

Plot No 11 A, Sector - III, Vaishali, Ghaziabad, U.P - 201010, (INDIA)

Office No 27, 31st Floor, API World Tower, Sheikh Zayed Road
Dubai (UAE), Near Conrad Hotel

Email: export@cleonpowertech.in, cleonpowertech@gmail.com

Website: www.cleonglobal.com

Customer Care No: +91- 8287141365, +971- 509141365