

PREMIUM SERIES

APPLICATION

- **▶** HOME APPLIANCES
- ▶ POWER BACK-UP
- ► OFFICE EQUIPMENT
- **▶** SECURITY INSTRUMENTS
- **▶** EMERGENCY LIGHTING
- **▶** SOLAR













Low Maintenance



Increased Back-Up



Superior Voltage



Longer Life



Aesthetic Design



Partial State of Charge Condition




Faster Recharge



Patented Container



PREMIUM SERIES





RANGE AVAILABE 50 AH 240 AH



- 1. LONG SHELF LIFE- HEAVE DUTY TUBULAR PLATES TO PROVIDE EXCELLENT CYCLIC LIFE WITH DEEP CYCLE CAPABILITIES.
- 2. EXCELLENT PERFORMANCE UNDER EXTREME TEMPERATURE CONDITIONS.
- 3. THICK SPINES FOR EXCELLENT DISCHARGE PERFORMANCE ON HEAVY LOADS.
- 4. SPECIALLY DESIGNED VENT PLUGS FOR MINIMUM ACID FUMES MOST COMPACT TALL TUBULAR DESIGN WITH GLOBAL ACCEPTABILITY.
- 5. LEAK PROOF HEAT SEALED TALL PP CONTAINER.
- 6. SPECIAL ALLOYS FOR LOW MAINTENANCE OF BATTERIES.
- 7. DARAMIC PE SEPARATOR WITH HIGH POROSITY,, LOW ELECTRICAL RESISTANCE AND EXCELLENT OXIDATION RESISTANT.
- 8. EXTRA THICK SPINES CAST AT HIGH PRESSURE TO ENSURE MINIMUM CORROSION FOR RELIABILITY, EXTRA-LONG LIFE AND STRENGTH.
- 9. CERAMIC FIAME ARREST OR PREVENTS ELECTRICAL SPARK TO GO IN AND THEREFORE ENSURES HIGHEST DEGREE OF SAFETY FOR ALL DOMESTIC.

 10. PATENTED DESIGN.

TECHNICAL DATA

CONTAINER TYPE	CAPACITY @ C10 AT 27°C AH	CONTAINER DIMENSION L/W/H IN MM	LIFE CYCLE @ 80% DOD	GROSS BATTERY WEIGHT +/- 3%	BACKUP
N 150	12V 70 AH	510X285X285	1800+	35 KG	2HR:10 MIN @ 200 WATT
N 200	12V 100 AH	520X290X280	1800+	52 KG	2HR:10 MIN @ 400 WATT
IT 500	12V 100 AH	510X190X440	1800+	54 KG	2HR:30 MIN @ 400 WATT
IT 500	12V 120 AH	510X190X440	1800+	56 KG	2HR:40 MIN @ 400 WATT
IT 500	12V 150 AH	510X190X440	1800+	60 KG	3HR:25 MIN @ 400 WATT
IT 500	12V 180 AH	510X190X440	1800+	63 KG	4HR:00 MIN @ 400 WATT
IT 500	12V 200 AH	510X190X440	1800+	65 KG	5HR:25 MIN @ 400 WATT
IT 500	12V 220 AH	510X190X440	1800+	69 KG	6HR:00 MIN @ 400 WATT
IT 500	12V 240 AH	510X190X440	1800+	72 KG	6HR:20 MIN @ 400 WATT

Plot No 11 A, Sector - III, Vaishali, Ghaziabad, U.P - 201010, (INDIA)

Office No 27, 31st Floor, API World Tower, Sheikh Zayed Road Dubai (UAE), Near Conrad Hotel Email: export@cleonpowertech.in, cleonpowertech@gmail.com

Website: www.cleonglobal.com

Customer Care No: +91- 8287141365, +971- 509141365

THIS CATALOGUE IS ISSUED TO PROVIDE OUTLINE INFORMATION ONLY AND IS NOT PART OF ANY OFFER OR CONTRACT. OUR POLICY IS ONE OF CONTINUED IMPROVEMENT AND WE RESERVE THE RIGHT TO CHANGE DETAILS WITHOUT PRIOT NOTICE.

COLOR OF THE PRODUCT MAY VARY FROM THE ORIGINAL COLOR IN THIS DOCUMENT.